

Sealed Alum Rivets



Rating: Not Rated Yet
Price:

[Ask a question about this product](#)

Description

STANDARD SEALED ALUM STEEL

3.2 STANDARD SEALED ALUMINIUM RIVET

d1	L	GRIP	HOLE	d2 (+0/-0.7)	k (+0.15)	p	d3
3.2	6.5	0.5-2.0	3.3	6.0	±1.4	≥27	1.7
3.2	8.0	2.0-3.5	3.3	6.0	±1.4	≥27	1.7
3.2	9.5	3.5-5.0	3.3	6.0	±1.4	≥27	1.7
3.2	10.7	5.0-6.5	3.3	6.0	±1.4	≥27	1.7
3.2	12.7	6.5-8.0	3.3	6.0	±1.4	≥27	1.7

4.0 STANDARD SEALED ALUMINIUM RIVET


d1	L	GRIP	HOLE	d2 (+0/-0.7)	k (+0.15)	p	d3
4.0	8.0	0.5-3.5	4.1	8.0	±1.7	≥27	2.16
4.0	9.5	3.5-6.5	4.1	8.0	±1.7	≥27	2.16
4.0	11.0	6.5-9.5	4.1	8.0	±1.7	≥27	2.16
4.0	12.7	8.5-10.0	4.1	8.0	±1.7	≥27	2.16
4.0	15.0	10.0-10.5	4.1	8.0	±1.7	≥27	2.16

4.8 STANDARD SEALED ALUMINIUM RIVET

d1	L	GRIP	HOLE	d2 (+0/-0.7)	k (+0.15)	p	d3
4.8	4.0	1.0-3.0	4.9	9.5	±2.0	≥27	2.63
4.8	6.0	3.0-4.5	4.9	9.5	±2.0	≥27	2.63
4.8	8.0	4.5-6.0	4.9	9.5	±2.0	≥27	2.63
4.8	10.0	6.0-7.5	4.9	9.5	±2.0	≥27	2.63
4.8	12.0	7.5-9.0	4.9	9.5	±2.0	≥27	2.63
4.8	14.0	9.0-11.0	4.9	9.5	±2.0	≥27	2.63
4.8	16.0	11.0-13.0	4.9	9.5	±2.0	≥27	2.63
4.8	18.0	13.0-16.0	4.9	9.5	±2.0	≥27	2.63
4.8	20.0	16.0-20.0	4.9	9.5	±2.0	≥27	2.63

6.4 STANDARD SEALED ALUMINIUM RIVET

d1	L	GRIP	HOLE	d2 (+0/-0.7)	k (+0.15)	p	d3
6.4	12.5	1.5-6.0	6.5	12.7	±2.5	≥31	3.7
6.4	16.0	6.0-8.0	6.5	12.7	±2.5	≥31	3.7



Standard rivet (all sizes in mm)

- d1 = rivet body diameter
- d2 = head diameter
- d3 = mandrel diameter
- k = head height
- L = rivet body length
- p = mandrel length

Reviews

There are yet no reviews for this product.